


FFW BASIC FLAT WELD TO THREAD

Flat weld mounts to reservoir ~ Sizes from 3/4" to 6" SAE/ISO/BSP




The **FFW Fixed Flat Weld** adapter provides much of the functionality of SFW without the swivel feature. For flat weld applications, see the complete array of Reservoir Weld adapters starting on page 26.

- Valves can be absent during welding to eliminate contamination and heat damage
- Reduced skilled labor requirement and improved repeatability for all skill classes
- Made in USA for fast delivery and top quality in sizes up to 6"
- Suction to 400 PSI



FFW		Basic Flat Weld to SAE/ISO/BSP Thread				
Part Number		Port Size	Dimensions IN			
SAE	ISO-6149		A	B	C	Lbs
FFW-07S	FFW-07IU	3/4"	1.38	0.63	0.75	0.20
FFW-10S	FFW-10IU	1"	1.63	0.63	1.06	0.30
FFW-12S	FFW-12IU	1 1/4"	2.00	0.63	1.25	0.40
FFW-15S	FFW-15IU	1 1/2"	2.25	0.63	1.50	0.50
FFW-20S	FFW-20IU	2"	2.75	0.63	2.00	0.70
FFW-25S	FFW-25IU	2 1/2"	3.38	0.63	2.50	1.00
FFW-30S	FFW-30IU	3"	4.00	0.75	3.00	1.70
FFW-40S	FFW-40IU	4"	5.00	0.75	4.00	2.20



Ordering Codes

FFW - ****** **S** - **1** **1**

Size Code	
Code	Port Size
07	3/4"
10	1"
12	1 1/4"
15	1 1/2"
20	2"
25	2 1/2"
30	3"
40	4"
50	5" - Call
60	6" - Call

External Thread-M	
Code	Description
S	Swivel SAE-M ORB
IU	Swivel ISO6149-M
B	Swivel BSPP-M

Adapter Material	
Code	Description
1	Low Carbon Steel
2	Stainless Steel

O-Ring Elastomer	
Code	Description
1	Buna-N (standard)
2	Ethylene Propylene "EPR"
3	Viton

Choose Adapter Size
Replace ** with the desired adapter size.

Alternate External Thread Standard

Replace the "S" SAE ORB standard thread connection with a choice from the "Thread Side" table. Please call to confirm price and availability.

Alternate Weld Connection Standard

DMIC does not offer any alternate weld connections for the **FFW** model adapter. For a Socket Weld variation, see **SSW** on page 7.

Due to our policy of continual product improvement, the specifications in this catalog may change without notice. When designing by spec, please request a certified print.

